

Product profile

CK32c

Intrinsically Safe Mobile Computer



- **Designed from inception to meet the most stringent, global certifications - UL, ATEX, IECEX**
- **Safest choice for workers in the chemical, oil and gas, and pharmaceutical industries**
- **Complements existing hazardous-certified and standard products allowing companies to standardize on one vendor or one form factor**
- **Supported by localized Intermec and Partner Service and Support Centers situated around the globe**

The Intermec CK32 Intrinsically Safe (CK32ISc) mobile computer carries the most extensive list of global hazardous environmental ratings of any rugged mobile computer in the world - UL (Underwriter's Laboratory), ATEX (European Atmospheres Explosibles Directives) and IECEX (International Electrotechnical Commission) - making it the safest choice for workers in the chemical, oil and gas, and pharmaceutical industries.

The CK32ISc meets or exceeds the most stringent requirements, not only for gases, vapors and liquids, but also for dusts, fibers and even, in certain regions, underground mining applications.

The highly durable construction of the CK32ISc reflects the operational reality of these environments: breakage in a hazardous location is more than a matter of downtime and inconvenience; it's potentially lethal. The rugged CK32ISc has achieved an IP67 sealing and 5 foot drop spec, and is the only mobile computer to achieve Zone 0 certification, which designates "double fault" safety in environments in which flammable gases are always present under normal operating conditions.

The CK32ISc provides the optimum combination of real time operation, tools support and standard connectivity by incorporating all the leading industrial mobile computing technologies - Microsoft® Windows Mobile® operating system, 802.11 b/g, Bluetooth®, integrated scanning, USB and Ethernet.

The intelligent design of the CK32ISc also allows users to easily install or remove scan handles and to replace batteries within a hazardous environment.

The CK32ISc is complemented by the full Intermec family of rugged ADC devices for the enterprise, as well as additional mobile computers for hazardous environments. This allows customers to simply pick the appropriate form factor and certifications ratings for their specific application needs.

The CK32ISc supports all the leading industry standards and development tools provided within Intermec's product offerings: SmartSystems™, Wavelink Avalanche Remote Device Management, Cisco® Compatible Extensions (CCX), Wi-Fi®, .NET, Java and the Intermec Developer Library (IDL). This commitment allows customers to further maximize

their investments by providing a strategy for ongoing, industry-leading technology updates, as well as support for fast application development and deployment. With the backing of Intermec's global service and support network for all products including the CK321Sc, customers can confidently implement a long term, reliable solution across multiple operational environments and take advantage of the efficiencies of less product training, fewer product platforms, and simplified support and service.

Physical Description

The CK321Sc is a rugged, intrinsically safe handheld mobile data collection computer, designed from inception to meet the most stringent global hazardous location requirements. It features the Windows Mobile 5.0 operating system and an Intel™ XScale™ PXA270 processor.

Physical Characteristics

Length: 240 mm (9.45 in)
Height: 51 mm (2.02 in) at grip area
Width at grip: 71 mm (2.8 in)
Weight: 1.08 kg (38 oz)

Hardware

Microprocessor: Intel XScale PXA270 Processor
Memory: 128 MB DRAM, 64 MB non-volatile Flash
Memory/Storage extensions: 512MB embedded SD
Flash Memory Card
Display: 240 x 320 (1/4 QVGA) backlit transfective display with 3.5" diagonal supporting 16-bit color depth (65K colors) and resistive panel touch screen. Tethered stylus included.
Keypad: 42-key and 56 key with Standard, VT/ANSI, 3270/5250 Overlay Configurations

Operating System

Microsoft® Windows Mobile 5.0

Software

Terminal Emulation: Supports Intermec TE2000 and third party VT/ANSI, IBM 5250/ 3270.
Browser support: Internet Explorer Mobile
Software Development Kit: Intermec Development Library (IDL). Supports device specific features and bar code scanning.

Bar Code Scanning

Integrated Linear Imager

Standard Communications

Ethernet
USB Client
Bluetooth®
802.11 b/g

Wireless Certifications

Wi-Fi
WPA2
Cisco Compatible Extensions CCX v3

Device Management

SmartSystems™ Support: Centralized remote support capability; Configures, updates and maintains single devices or entire populations; Real-time or batch, wired or wireless; Wavelink Avalanche™ with Intermec's value added utilities

Power

Battery Type: Lithium-Ion, 7.5V, 2400 mAh; User replaceable in hazardous environments

Environment

Operating Temperature: -20° to 50°C (-4° to 122°F)
Storage Temperature: -20° to 70°C (-4° to 158°F)
Relative humidity: 5 - 95% (non-condensing)
Environmental protection: IP67
Drop Survival: Multiple 5' (1.52 m) drops to ¼ inch steel plate bonded to a concrete slab
Vibration and shock protection: Tested to MIL-PRF-28800F standards

Accessories

Chargers: Model AC11 4-slot battery charger
Communications Adapter Model AN1: Required for USB and Ethernet.
User Accessories: Pistol grip handle; carrying strap; hand strap; user replaceable touch panel protection cover, AB6 spare battery, battery eliminator

Regulatory Compliance

Compliant with all EU Directives including ATEX IECEx Certified
FCC Part 15/ICES-003/EN55022/CISPR 22 Class A
UL 913 Certified

Regulatory Compliance - Pending
NOM-NYCE

Hazardous Location Certifications (ATEX/IECEx)

Zone 0, IIC, T4
Zone 20, T250°C
Group I M1

ATEX Countries

Approved: Europe, Turkey, Norway, Switzerland, Czech Republic

IECEx Countries

Approved: New Zealand, Australia, Singapore, Malaysia
Pending: Saudi Arabia, South Africa, Thailand, UAE, Brazil, China, South Korea, Indonesia, Philippines

Hazardous Location Certifications (UL)

Class I, Division 1, Groups A, B, C, D - T4
Class I, Zone 0, Group IIC, T4
Class II, Division 1, Groups E, F, G - T4
Class III, Division 1

UL Countries

Approved: U.S., Canada
Pending: Mexico

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico

Headquarters Office
Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Intermec®
SmartSystems™



Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611825-01D 03/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec®